ALASKA REQUIREMENTS SUMMARY					
Requirement	Boats under 16 feet	Boats 16 to less than 26 feet	Boats 26 to less than 40 feet	Boats 40 to less than 65 feet	
Personal Flotation Devices	One USCG approved Type I,II,III, or V PFD of the proper size for each person, in serviceable condition, and readily accessible. <u>Persons under 13 must wear</u> their PFD when in an open boat or on the deck of a boat, and when waterskiing.				
Throwable Personal Flotation Device (Type IV)	Recommended but not (seat cushion or throw ring) device must be carried. Whistle, horn, or bell, or some other means to make an Whistle or horn,				
Sound Producing Device	efficient sound sign	Whistle, horn, or bell, or some other means to make an efficient sound signal.			
Visual Distress Signals	USCG approved night signals required between sunset and sunrise.	length (that are not equipped with mechanical propulsion), are not required to carry day signals but must carry USCG approved signals for night time use. All others must carry			
Fire Extinguishers	At least one USCG approved B-I required for boats with inboard engines, living spaces, permanent fuel tanks, or enclosed storage areas or hull voids not sealed or filled with flotation material. At least two B-I or one B-I USCG approved fire extinguishers. At least two B-I or one B-I uscG approved fire extinguishers.				
Navigation Lights	Display required between sunset and sunrise and during periods of restricted visibility. International configuration required (varies with length and mode of operation). See the International Navigation Rules.				
Backfire Flame Arrester	One USCG approved backfire control device on each carburetor of all inboard gasoline engines.				
Ventilation	Boats with permanently installed engines, closed compartments, or permanent fuel tanks, must have efficient natural or mechanical ventilation.				
Registration	Undocumented boats equipped with mechanical propulsion (gas, diesel or steam engines and electric motors) must be registered with the Division of Motor Vehicles. Certificate of Number must be carried on board. Registration numbers and validation decals must be properly displayed.				